



ProGem™ LED Linear High Bay

Illuminate indoor areas day and night with ProGem™ Technology. Engineered for high LED lumen output with long-rated life. Smart Ready for daylight, bi-level dimming, motion and occupancy sensor functions.

Features

Sizes	2 ft and 4 ft
Finish	Pure White Semi-Gloss
Diffuser	Anti-UV Frosted Polycarbonate Lens
Rated Life	75000 hours
Warranty	7 years

Construction

Manufactured for durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

Applications

Primary use as high-bay luminaires for commercial and industrial buildings. Pendant or surface mounted specifically for indoor high ceiling spaces above 25 feet.

Listings

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. View DLC Premium listing at: designlights.org/qpl

Warranty

7 year exclusive limited warranty.



Performance

Wattage	See ordering information.
Voltage	120-277V or 277-480V
Frequency	50/60 Hz
Efficacy	≥ 140 lm/W
CCT	4000K or 5000K
CRI	≥ 80
Power Factor	≥ 0.9
THD	≤ 15%
Operating Temp.	-20° C to 40° C (-4° F to 104° F)
Dimming	0-10V

ORDERING INFORMATION

Model No.	Wattage (W)	Voltage (V)	CCT (K)	Light Output	Efficacy (lm/w)	Rated Life
ETH-B02-80W-H-4000K	80W	120-277V	4000K	11200 lm	140 lm/W	75000 hrs
ETH-B02-80W-H-5000K	80W	120-277V	5000K	11200 lm	140 lm/W	75000 hrs
ETH-B02-80W-H-5700K	80W	120-277V	5700K	11200 lm	140 lm/W	75000 hrs
ETH-B03-110W-H-4000K	110W	120-277V	4000K	15400 lm	140 lm/W	75000 hrs
ETH-B03-110W-H-5000K	110W	120-277V	5000K	15400 lm	140 lm/W	75000 hrs
ETH-B03-110W-H-5700K	110W	120-277V	5700K	15400 lm	140 lm/W	75000 hrs
ETH-B05-165W-H-4000K	165W	120-277V	4000K	23100 lm	140 lm/W	75000 hrs
ETH-B05-165W-H-5000K	165W	120-277V	5000K	23100 lm	140 lm/W	75000 hrs
ETH-B05-165W-H-5700K	165W	120-277V	5700K	23100 lm	140 lm/W	75000 hrs
ETH-B06-220W-H-4000K	220W	120-277V	4000K	30800 lm	140 lm/W	75000 hrs
ETH-B06-220W-H-5000K	220W	120-277V	5000K	30800 lm	140 lm/W	75000 hrs
ETH-B06-220W-H-5700K	220W	120-277V	5700K	30800 lm	140 lm/W	75000 hrs
ETH-B01-110W-HV-H-4000K	110W	347-480V	4000K	15400 lm	140 lm/W	75000 hrs
ETH-B01-110W-HV-H-5000K	110W	347-480V	5000K	15400 lm	140 lm/W	75000 hrs
ETH-B01-110W-HV-H-5700K	110W	347-480V	5700K	15400 lm	140 lm/W	75000 hrs
ETH-B04-220W-HV-H-4000K	220W	347-480V	4000K	30800 lm	140 lm/W	75000 hrs
ETH-B04-220W-HV-H-5000K	220W	347-480V	5000K	30800 lm	140 lm/W	75000 hrs
ETH-B04-220W-HV-H-5700K	220W	347-480V	5700K	30800 lm	140 lm/W	75000 hrs
ETH-B07-225W-HV-H-4000K	225W	347-480V	4000K	31500 lm	140 lm/W	75000 hrs
ETH-B07-225W-HV-H-5000K	225W	347-480V	5000K	31500 lm	140 lm/W	75000 hrs
ETH-B07-225W-HV-H-5700K	225W	347-480V	5700K	31500 lm	140 lm/W	75000 hrs
ETH-B10-320W-HV-H-4000K	320W	347-480V	4000K	44800 lm	140 lm/W	75000 hrs
ETH-B10-320W-HV-H-5000K	320W	347-480V	5000K	44800 lm	140 lm/W	75000 hrs
ETH-B10-320W-HV-H-5700K	320W	347-480V	5700K	44800 lm	140 lm/W	75000 hrs