



## TriLum™ Tunable LED Troffer Retrofit

Illuminate indoor areas day and night with TriLum™ Tunable Technology. Easily switch settings between lighting hues and input wattage to create that perfect glow. Engineered for balanced LED lumen output with long-rated life. Smart Ready for daylight, bi-level dimming, motion and occupancy sensor functions.

### Features

Sizes	2x2 and 2x4
Finish	Pure White Satin
Diffuser	Shatterproof Frosted Polycarbonate Lens
Rated Life	75000 hours
Warranty	7 years

### Construction

Manufactured for durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

### Applications

Primary use as 2x2 and 2x4 luminaires for ambient lighting of interior commercial spaces. Intended to provide ambient lighting in settings such as office spaces, schools, retail stores, and other commercial environments.

### Listings

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. View DLC Premium listing at: [designlights.org/qpl](https://designlights.org/qpl)

### Warranty

10 year exclusive limited warranty. View complete product warranty information at: [etheriumled.com/warranty](https://etheriumled.com/warranty)



### Performance

Wattage	See ordering information.
Voltage	120-277V
Frequency	50/60 Hz
Efficacy	130 lm/W
CCT	Tunable (3500K, 4000K, or 5000K)
CRI	> 80
Power Factor	≥ 0.9
THD	< 20%
Operating Temp.	-20°C to 40°C (-4°F to 104°F)
Dimming	0-10V

## ORDERING INFORMATION

Model No.	Size	Wattage (W)	Voltage (V)	CCT (K)	Light Output	Efficacy (lm/w)	Rated Life
ETH-TTRK-22-30W	2x2	20	120-277V	3500K, 4000K, 5000K	2600 lm	130 lm/W	75000 hrs
		25	120-277V	3500K, 4000K, 5000K	3250 lm	130 lm/W	75000 hrs
		30	120-277V	3500K, 4000K, 5000K	3900 lm	130 lm/W	75000 hrs
ETH-TTRK-24-34W	2x4	25	120-277V	3500K, 4000K, 5000K	3250 lm	130 lm/W	75000 hrs
		30	120-277V	3500K, 4000K, 5000K	3900 lm	130 lm/W	75000 hrs
		34	120-277V	3500K, 4000K, 5000K	4420 lm	130 lm/W	75000 hrs