



## DuraGem™ LED Wall Pack

Illuminate outdoors from dusk to dawn with proprietary DuraGem™ Technology. Engineered for balanced LED lumen output with long-rated life. IP65 Rated for wet locations. Smart Ready for photocell and bi-level dimming functions.

### Features

IP Rating	IP65 - Wet Location
Finish	Dark Bronze Satin
Diffuser	Anti-UV Prismatic Tempered Glass Lens
Rated Life	50000 hours
Warranty	5 years

### Construction

Manufactured for weather-proof durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

### Applications

Primary luminaire use as outdoor non-cutoff and semi-cutoff wall-mounted for walkways or security lights that produces a non-negligible amount of uplight.

### Listings

DLC listed. ETL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. IP65 rated for wet location use. View DLC listing at: [designlights.org/qpl](https://designlights.org/qpl)

### Warranty

5 year exclusive limited warranty



### Performance

Wattage	See ordering information.
Voltage	120-277V
Frequency	50/60 Hz
Efficacy	105 lm/W
CCT	4000K or 5000K
CRI	≥ 80
Power Factor	≥ 0.9
THD	≤ 15%
Operating Temp.	-40°C to 45°C (-40°F to 113°F)
Dimming	0-10V

## ORDERING INFORMATION

Model No.	Wattage (W)	Voltage (V)	CCT (K)	Light Output	Efficacy (lm/w)	Rated Life
ETH-E02-40W-H-4000K	40	120-277V	4000K	6000 lm	150 lm/W	50000 hrs
ETH-E02-40W-H-5000K	40	120-277V	5000K	6000 lm	150 lm/W	50000 hrs
ETH-E02-60W-H-4000K	60	120-277V	4000K	9200 lm	145 lm/W	50000 hrs
ETH-E02-60W-H-5000K	60	120-277V	5000K	9250 lm	145 lm/W	50000 hrs
ETH-E03-80W-H-4000K	80	120-277V	4000K	11550 lm	145 lm/W	50000 hrs
ETH-E03-80W-H-5000K	80	120-277V	5000K	11625 lm	145 lm/W	50000 hrs
ETH-E04-100W-H-4000K	100	120-277V	4000K	13670 lm	145 lm/W	50000 hrs
ETH-E04-100W-H-5000K	100	120-277V	5000K	13950 lm	145 lm/W	50000 hrs