



TriLum™ Tunable LED Troffer

Illuminate indoor areas day and night with TriLum™ Tunable Technology. Easily switch settings between lighting hues and input wattage to create that perfect glow. Engineered for balanced LED lumen output with long-rated life.

Features

Sizes	2x2 and 2x4
Finish	Pure White Satin
Diffuser	Anti-UV Frosted Polycarbonate Lens
Rated Life	50000 hours
Warranty	5 years

Construction

Manufactured for durability using aluminum housing with satin anti-UV polyester coating to resist corrosion, discoloration, and scratching. Smart options for bi-level dimming, motion sensor and emergency functions.

Applications

Primary use as 2x2 and 2x4 luminaires for ambient lighting of interior commercial spaces. Ideal for offices, retail and other architectural spaces.

Listings

ETL and DLC certified. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. View DLC listing at: designlights.org/qpl

Warranty

5 year exclusive limited warranty. View complete product warranty information at: etheriumled.com/warranty



Performance

Wattage	See ordering information.
Voltage	120-277V
Frequency	50/60 Hz
Efficacy	130 lm/W
CCT	Tunable (3000K-5000K)
CRI	> 80
Power Factor	≥ 0.95
THD	< 15%
Operating Temp.	-20°C to 40°C (-4°F to 104°F)
Dimming	0-10V

ORDERING INFORMATION

Mode	Power	Input Voltage	Dimmable	Input Current	PF	Light Efficacy	Ra	CCT
GL-TTR-22-40W-L-H	25-30-35-40W	AC100-277V	0-10V	0.4A	>0.9	130lm/w	80	3000K-5000K
GL-TTR-24-50W-L-H	35-40-45-50W	AC100-277V	0-10V	0.5A	>0.9	130lm/w	80	3000K-5000K