

## **LED SURFACE MINI PANEL**

▶ **DESIGN & OPTIONS** - LED SURFACE MINI PANEL has a classic, low-profile design that gives it a sleek look with efficient lighting. The modern LED dimmers provide smooth dimming capabilities ranging from 10% to 100%. The 120° beam angle grants you smooth and even lighting. It is also CCT selectable, letting you set it to 3,000K, 4,000K or 5,000K with a simple switch. This fixture comes in four sizes: 5°, 7°, 9° and 12°, and a WHITE or BLACK finish.



Models with a built-in PIR motion sensor automatically turn off in the



Models with a built-in battery back-up provide 90 minutes of power in case of emergency.

- ▶ INSTALLATION Installation is quick and easy: just attach the bracket to the outlet box with screws, connect the wires, and fix the lamp on the bracket. Screws, wire nuts and all installation accessories are provided. The fixture can be installed on either an existing outlet box or a remodeled can by using a retrofit kit with universal TP24 or E26 connectors (sold separately). Refer to install instructions for detailed steps.
- ▶ **APPLICATION** The LED SURFACE MINI PANEL provides bright, yet smooth lighting for your family room, bedroom, hallway, corridor, or any other common area in your living space. It is also suitable for Damp Locations, making it perfect for kitchens and garages as well. It can also be used as additional lighting to an already existing ceiling light.
- ▶ ENERGY SAVINGS & EFFICIENCY With a lifespan of 50,000 hours, these fixtures are made to last decades under normal operation! This fixture can cut your electric bill by up to 80% instantly and will save you a significant amount of money in its lifetime.
- ▶ CERTIFICATION & WARRANTY Buy with confidence: ASD provides a 5-year limited warranty along with ETL certification to guarantee top quality products and safety!

Energy Star classification allows participation in rebates; please check the rebate programs available in your state.

Catalog number	
Notes	
Туре	











Model	Watts	Voltage	Dimmable	Lumens	CCT	Finish	Dimensions (LxWxH)	Type	Options	
MPR ROUND										
ASD-MPR-5D10CC-WH	10W	120 V	TRIAC	667/754/695 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	5-5/16" x 5-5/16" x 1"	Round	-	
ASD-MPR-5D10CC-WH-6pack	10W	120 V	TRIAC	667/754/695 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	5-5/16" x 5-5/16" x 1"	Round	-	
ASD-MPR-7D15CC-WH	15W	120 V	TRIAC	1,061/1,364/1,152 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	7-1/8" x 7-1/8" x 1"	Round	-	
ASD-MPR-7D15CC-WH-6pack	15W	120 V	TRIAC	1,061/1,364/1,152 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	7-1/8" x 7-1/8" x 1"	Round	-	
ASD-MPR-7D15CC-BK	15W	120 V	TRIAC	1,061/1,364/1,152 lm	3CCT (3,000 K/4,000 K/5,000 K)	Black	7-1/8" x 7-1/8" x 1"	Round	=	
ASD-MPR-9D18CC-WH	18W	120 V	TRIAC	1,348/1,522/1,306 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	8-7/8" x 8-7/8" x 1"	Round	=	
ASD-MPR-9D18CC-WH-6pack	18W	120 V	TRIAC	1,348/1,522/1,306 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	8-7/8" x 8-7/8" x 1"	Round	=	
ASD-MPR-9D18CCA-BK	18W	120 V	TRIAC	1,348/1,522/1,306 lm	3CCT (3,000 K/4,000 K/5,000 K)	Black	8-7/8" x 8-7/8" x 1"	Round	=	
ASD-MPR-12D24CC-WH	24W	120 V	TRIAC	1,721/2,218/2,028 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	11-13/16" x 11-13/16" x 1"	Round	=	
					MPS SQUARE					
ASD-MPS-7D12CC-WH	12W	120 V	TRIAC	914/1,034/1,012 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	7-1/8" x 7-1/8" x 5/8"	Square	-	
ASD-MPS-7D12CC-WH-6pack	12W	120 V	TRIAC	914/1,034/1,012 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	7-1/8" x 7-1/8" x 5/8"	Square	-	
ASD-MPS-7D12CC-BK	12W	120 V	TRIAC	914/1,034/1,012 lm	3CCT (3,000 K/4,000 K/5,000 K)	Black	7-1/8" x 7-1/8" x 5/8"	Square	-	
ASD-MPS-9D18CC-WH	18W	120 V	TRIAC	1,139/1,276/1,229 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	8-7/8" x 8-7/8" x 5/8"	Square	=	
ASD-MPS-9D18CC-WH-6pack	18W	120 V	TRIAC	1,139/1,276/1,229 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	8-7/8" x 8-7/8" x 5/8"	Square	=	
ASD-MPS-9D18CC-BK	18W	120 V	TRIAC	1,139/1,276/1,229 lm	3CCT (3,000 K/4,000 K/5,000 K)	Black	8-7/8" x 8-7/8" x 5/8"	Square	=	
				MPR-MS RO	UND WITH MOTION SENSOR					
ASD-MPR-9N18CC-MS-WH	18W	120 V	-	1,300/1,430/1,340 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	8-3/4" x 8-3/4" x 3/4"	Round	Motion sensor	
				MPR-EM ROL	IND WITH BATTERY BACK-UP					
ASD-MPR-7D15CC-EM-WH	15W	120 V	TRIAC	1,122/1,209/1,111 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	7-1/8" x 7-1/8" x 1 3/4"	Round	6W Battery back up	
ASD-MPR-9D18CC-EM-WH	18W	120 V	TRIAC	1,412/1,674/1,437 lm	3CCT (3,000 K/4,000 K/5,000 K)	White	8-7/8" x 8-7/8" x 1 3/4"	Round	12W Battery back up	
ASD-SP7-MPR-WH	Sub-pl	Sub-plate for LED Round Surface Mini Panel 7"					7-1/8" x 7-1/8" x 1-3/4"	Round	-	

For most up-to-date spec sheets please refer to asd-lighting.com



